

## Communications & Power Industries CCTWT

The VTX-5682A pulsed-coupled cavity TWT covers 9.0 GHz to 9.5 GHz with 30 kW peak output power, 1.0% duty cycle. This device is Cathode pulsed with a isolated collector to achieve 48 dB gain.

Custom configurations are also available. These variations in the performance and configuration include: grid modulation, cooling method (affects average power level), mechanical configuration, electrical and RF connections.

Contact us at [MPPMarketing@cpii.com](mailto:MPPMarketing@cpii.com) or call us at +1 650-846-2800.

### Typical Operating Parameters

PARAMETER	MIN	MAX	UNITS
Cathode Voltage	-27	-25	kV
Cathode Current	---	7.0	a
Heater Voltage	9	11	V
Heater Current	---	4	A
RF Drive Power	---	0.25	W
Pulse Width	---	50	µsec
Duty Cycle	---	1.0	%
Cooling Flow Rate	2.0	---	lbm/min
Pressure Drop	---	2.5	In H <sup>2</sup> O
Weight	---	16	lbs
Dimensions	---	4 X4X18	inches

### FEATURES:

- 9.0 GHz to 9.5 GHz
- 30 kW Peak output power
- 1.0% Duty cycle
- Cathode pulsed
- 48 dB gain
- Isolated collector
- Forced air cooled
- PPM focused
- WR 90 waveguide, input and output

### BENEFITS:

- Efficient
- Bandwidth
- Over 40 years of technical expertise

### APPLICATIONS:

- Ground radars



**Microwave Power  
Products Division**  
3120 Hansen Way  
Palo Alto, California  
USA 94303

tel +1 650-846-2800  
fax +1 650-856-0705  
email [MPPMarketing@cpii.com](mailto:MPPMarketing@cpii.com)  
web [www.cpii.com/MPP](http://www.cpii.com/MPP)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.